



CB04/03394

INVESTOR IN PEOPLE

The Patent Office Concept House Cardiff Road Newport South Wales

NP10 8QQ

REC'D 27 SEP 2004

WIPO PCT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed


Dated

14 September 2004

PRIORITY DOCUMENT

SUBMITTED OR TRANSMITTED IN COMPLIANCE WITH RULE 17.1(a) OR (b)

·					
			, t		
		i.			
					_
				. 17	
			*		





150EC03 EB59284+1 D01070 F01/7700 0.00-0238937/8 ACC

Request for grant of a patent (See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

13 DEC 2003

NEWPORT

The Patent Office

Cardiff Road Newport Gwent NP9 1RH

		· .
1.	Your reference	P4242.A1/DCC
2.	Patent application number (The Patent Office will fill in this part)	0328937.8
3	Full name, address and postcode of the or of each applicant (underline all surnames)	Checkmate UK Limited New Road New Road Industrial Estate SHEERNESS
	Patents ADP number (if you know it)	ME12 1PZ UNITED KINGDOM
	If the applicant is a corporate body, give the country/state of its incorporation	UNITED KINGDOM 7009488002
4.	Title of the invention	Lifeline Trolley
5.	Name of your agent (if you have one)	DUMMETT COPP
	"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)	25 THE SQUARE MARTLESHAM HEATH IPSWICH IP5 3SL
	Patents ADP number (if you know it)	6379001
6.	If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number	Country Priority application number Date of filing (if you know it) (day / month / year)
7.	If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of	Number of earlier application Date of filing (day / month / year)
	the earlier application	
8.	Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if: a) any applicant named in part 3 is not an inventor, or	YES
-	 b) there is an inventor who is not named as an applicant, or c) any named applicant is a corporate body. See note (d)) 	

Patents Form 1/77

Enter the number of sheets for any of the 9. following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description

Claim(s)

5

Abstract

Drawing(s)

re Ho

If you are also filing any of the following, 10. state how many against each item.

Priority documents

Translation of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77)

Request for substantive examination (Patents Form 10/77)

> Any other documents (please specify)

> > I/We request the grant of a patent on the basis of this application.

DUMMETT COPP

December 2003

12. Name and daytime telephone number of person to contact in the United Kingdom David Copp 01473 660600

Warning

11.

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

Lifeline Trolley

This invention relates to a trolley adapted to travel along a lifeline set up to allow personnel to connect their safety harnesses to the trolley, so that they can move about while still being connected to the lifeline, through the trolley.

According to the invention, there is provided a trolley having a channel adapted to fit over a lifeline, an means for connecting a lifeline harness to the trolley and a brake activated by movement of the connecting means relative to the trolley, to brake the trolley relative to the lifeline.

15

The trolley is preferably adapted to run on a generally horizontal lifeline.

The connecting means preferably comprises an elongate aperture through a body of the trolley, with a movable finger traversing the aperture and with the harness lifeline connected to the finger and movable in the aperture so that movement of the finger relative to the aperture activates the brake.

25

30

The brake preferably comprises a cam mounted for pivoting movement in the trolley body, with the movable finger forming part of the cam, and another part of the cam projecting into the channel to engage the lifeline, when he finger moves to rotate the cam.



The cam preferably has two fingers, both of which traverse the elongate aperture and the harness lifeline is located between the two fingers so that movement of the harness lifeline in either direction causes the cam to rotate.

The cam is preferably symmetrical about a vertical axis.

5

The trolley may include a karabiner fitted in the aperture, with a limb of the karabiner located between the two fingers of the cam. A user can then clip his harness lifeline into the karabiner.

The channel for accommodating the lifeline wire preferably

15 has an opening at one point around its circumference to
allow the trolley to pass a lifeline support bracket. the
opening is preferably at a part of the circumference where
it will not lie against the lifeline during use.

- 20 The invention will now be further described, by way of example, with reference to the accompanying drawings, in which:
- Figure 1 is a first perspective view of a trolley according to the invention on a lifeline;
 - Figure 2 is a second perspective view of the trolley of Figure 1;
- 30 Figure 3 is a third perspective view of the trolley

	1	
		ı

of Figure 1;

Figure 4 is a longitudinal section through the trolley; and

Figure 5 is a transverse section through the trolley.

Figure 1 shows a trolley generally designated 10 in place on a wire lifeline 12. The lifeline will be tensioned 10 between brackets on a structure where workmen will be working above the ground, in a manner which is well known. The trolley 10 has a body with a tubular portion 14 within which the lifeline 12 is received. The tubular portion 14 is able to slide freely in either direction along the lifeline. The tubular portion also has a mouth 16 (see particularly Figure 5) which is too narrow to allow the trolley to be removed from the lifeline 12, but which will allow the trolley to pass lifeline support brackets (not shown), in a manner known per se.

20

25

A lower portion of the body has an aperture 18 into which a lifeline harness can be connected. In the figures, a karabiner 20 is shown in position in the aperture 18. This karabiner may be permanently fixed to a user's harness lifeline, or another karabiner or other hook on the end of the harness lifeline may be connected into the karabiner 20. The latter is preferable.

Within the body of the trolley is a cam 22. As can be 30 seen in Figure 4, the cam has a fork 24 which extends

	•	
		7,,
•		

across the aperture 18. The cam is mounted for pivoting movement on an axle 26, and has a cam face 28. As can be seen in Figures 1 and 2 the karabiner 20 has a limb 20a which is located between the two limbs of the fork 24.

5 Under normal conditions, the cam 22 will be in the central position as shown in Figures 3 and 4, and the limb 20a of the karabiner will lie in a recess 30 of the aperture 18. However, if there is a sudden load on the karabiner, as a result of a workman falling or losing his balance, the larabiner will move to one or other end of the aperture 18, causing the cam 22 to pivot about the axis 26, where upon the cam face 28 projects into the cross-section of the tubular portion 14 and jams the trolley against the lifeline 12. This is shown in Figures 1 and 2.

15

To prevent this locking action happening too readily, which would obstruct normal motion of the trolley along the length of the lifeline 12, a spring loaded pin 32 normally holds the cam 22 in its middle position as shown in Figure 4. The pin 32 engages in a detent 34 in the cam. However, a sharp load on the cam will overcome the spring force which holds the pin 32 in the detent 34 so that the cam can move to one side or the other to lock the trolley to the lifeline. The recess 30 also helps gravity to keep the karabiner in the central position under normal conditions.

The trolley body is preferably a single cast component.


30 It will be noted that the mouth 16 of the tubular portion

		!
		·

14 is only open at a lower region of the tubular portion so that when a load comes on a trolley the lifeline is not pulled against the mouth 16. Also, the ends 14a and 14b of the slot 14 are chamfered so that when the trolley approaches a mounting bracket, it is caused to rotate about the axis of the lifeline to enable it to pass the mounting bracket.


All of these features make for a rugged trolley with a simple locking mechanism which will not lock on the lifeline unless it is subjected to a sudden snatch load. The level of load at which locking will take place can be adjusted by setting of the spring tension on the pin 32.


		1 1	
	·		
			·











PCT/632004/003394 6/6/04 DUMMETT COPP

PCT/GB2004/003394